

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
18 September 2003 (18.09.2003)

PCT

(10) International Publication Number
WO 03/076854 A1

(51) International Patent Classification⁷: F25B 9/00

(21) International Application Number: PCT/US03/06580

(22) International Filing Date: 5 March 2003 (05.03.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/361,651 5 March 2002 (05.03.2002) US

(71) Applicant (for all designated States except US): SHI-APD CRYOGENICS, INC. [US/US]; 1833 Vultee Street, Allentown, PA 18103-4783 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): GAO, Jin, Lin [US/US]; c/o Shi-APd Cryogenics, Inc., 1833 Vultee Street,

Allentown, PA 18103-4783 (US). LONGSWORTH, Ralph, C. [US/US]; Shi-APd Cryogenics, Inc., 1833 Vultee Street, Allentown, PA 18103-4783 (US).


(74) Agents: HELFGOTT, Samson et al.; Katten Muchin Zavis Rosenman LLP, 575 Madison Avenue, New York, NY 10022-2585 (US).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),

[Continued on next page]

(54) Title: FAST WARM UP PULSE TUBE



(57) Abstract: This invention provides an improved means of quickly warming a pulse tube (165) by shifting the phase relation of flow to the warm end of the pulse tube relative to flow to the warm end (117) of the pulse tube relative to flow to the warm end of the regenerator (160) using a "four valve" concept and the "active buffer" concept. Several different pulse tube configurations and valve timing relations that are effective at reversing the cycle from the normal mode, which produces cooling at the pulse tube heat station, to a reverse mode that produces heating are disclosed.



Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

— *before the expiration of the time limit for amending the
claims and to be republished in the event of receipt of
amendments*

Published:

— *with international search report*

*For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.*

regenerator. Not all pulse tube phase shifting mechanisms lend themselves to fast warm up by changing the valve timing. Surprisingly, there are several different pulse tube configurations and valve timing relations that are effective at reversing the cycle from the normal mode, which produces cooling at the pulse tube heat station, to a reverse mode that produces heating.

Two phasing mechanisms that lend themselves to fast warm up are the "four valve" concept and the "active buffer" concept. These were first described in the following papers, 1] Y. Matsubara, J. L. Gao, K. Tanida, Y. Hiresaki, and M. Kaneko, "An experimental and analytical investigation of 4 K pulse tube refrigerator", Proc. 7th Intl Cryocooler Conf., Air Force Report PL-(P-93-1001 (1993) pp. 166-186; and 2] S. W. Zhu, Y. Kakami, K. Fujioka, and Y. Matsubar, "Active-buffer pulse tube refrigerator", Proceedings of the 16th Cryogenic Engineering Conference, T. Haruyama, T. Mitsui and K. Yamafriji. ed. Eisevier Science. Oxford (1997), pp. 291-294.

A split rotary valve is disclosed that illustrates a simple means of providing the desired change of phase when it is turned in reverse. Single stage pulse tubes are used to illustrate the invention but the principals can be applied equally well to multi- stage pulse tubes.

Cryopumps, which are cooled by two stage pulse tubes that use this invention, can be quickly warmed up without the need for heaters.

Disclosed are several different pulse tube configurations and valve timing relations that are effective at reversing the cycle from the normal mode, which produces cooling at the pulse tube heat station, to a reverse mode that produces heating.

In one embodiment of the invention, a split rotary valve illustrates a simple means of providing the desired change of phase when it is turned in reverse.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a schematic of a single stage pulse tube that is known in the art as having "four valve" control and to which the present invention can be applied.

FIG. 2 is a schematic of a variation of the Figure 1 control scheme to which the present invention can be applied.

FIG. 3 is a schematic of a second variation of the Figure 1 control scheme to which the present invention can be applied.

FIG. 4 is a schematic of a single stage pulse tube that is known in the art as having "active buffer" control.

FIG. 5a is a pressure vs. volume (P-V) plot of the gas that enters the cold end of the Figure 1 pulse tube during the normal cooling mode.

FIG. 5b is a P-V plot of the gas that enters the cold end of the Figure 1 pulse tube during the heating mode per this invention.

FIG. 6 is a cross section of dual rotary valve that can implement the P-V plot shown in Figure 5.

FIG. 6a is a top view of the valve plate.

FIG. 6b and 6c show views from the back of each valve disc while it is rotating to produce cooling as shown in Figure 5a.

FIG. 6bb and 6cc show views from the back of each valve disc while it is rotating in reverse to produce heating as shown in Figure 5b.

DETAILED DESCRIPTION OF THE INVENTION

The present invention is applicable to G-M type pulse tubes that use valves to control the phase relationship of the flow to the warm end of the regenerator relative to the flow to the warm end of the pulse tube. By changing the phase relationship, the pulse tube can be made to shift from a cooling mode to a warming mode.

The single stage pulse tube shown in figure 1 illustrates an embodiment of the invention. Figure. 1 shows Pulse Tube Refrigerator 100, which is comprised of Regenerator 160, Pulse Tube 165, Connecting Tube 115. Gas Line 110, Gas Line 111, Valve 120, Valve 125, Valve 910, Valve 915, Cold Heat Station 116, and Hot Heat Station 117.

Gas Line 110 brings high-pressure gas from the compressor and Gas Line 111 returns gas at low pressure to the compressor. Valve 120 admits high-pressure gas to the warm end of Regenerator 160 and Valve 125 returns gas from the warm end of Regenerator 160 to the compressor. Valve 910 admits high-pressure gas to the warm end of Pulse Tube 165 and Valve 915 returns gas from the warm end of Pulse Tube 165 to the compressor. Connecting Tube 115 connects the cold end of Regenerator 160 with the cold end of Pulse Tube 165. Heat is picked up at the cold end of Pulse Tube 165 in Cold Heat Station 116. It may be transferred to ambient temperature from Hot Heat Station 117, or returned to the compressor through Valve 915.

Cooling is produced at the cold end of Pulse Tube Refrigerator 100 when the valve timing is approximately as shown in Table 1 under the heading "COOLING". With this timing the P-V relation for the gas flowing in and out of the cold end of Pulse Tube 165 is approximately as shown in Figure 5a. The phases when each of the valves is open are noted on Figure 5a.

A P-V plot that follows a clockwise path is known to produce work. The work is equal to the cooling that is produced and can be measured from the area of the P-V plot. Energy in the form of work is transferred from a low temperature to ambient temperature.

When the timing of opening and closing Valves 910 and 915 relative to Valves 120 and 125 is changed as shown in Table 1 under the heading listed "WARM UP", the P-V relation changes to approximately the plot shown in Figure 5b. This plot follows a counter clockwise path that transfers work energy from ambient temperature to the cold end of Pulse Tube 165. The heating is equal to the amount of work that is transferred and will cause the cold end of Pulse Tube 165 to warm up.

Figure 2 shows Pulse Tube Refrigerator 200 as a variation of the figure 1 control scheme in which Buffer Tank 180 is connected to the warm end of Pulse Tube 165. Valve 205 controls the timing of flow in and out of Buffer Tank 180. Valve timing for the normal cooling mode is shown in the upper part of Table 2 and timing for the warm up mode is shown in the lower part of Table 2. Adding Buffer Tank 180 and Valve 205 improves the efficiency of the pulse tube relative to Figure 1 by having some of the gas that flows to and from the warm end of the pulse tube come from Buffer Tank 180 rather than from the compressor. The P-V plots for cooling and heating are essentially the same as those shown in figures 5a and 5b. In the cooling mode,

this is accomplished by opening Valve 205 before opening Valve 190.

Figure 3 shows Pulse Tube Refrigerator 300 as a variation of Pulse Tube 200 in which Valve 205 is replaced with Fixed Restrictor 145. It serves the same function as Valve 205 but is less efficient because gas flows in and out of Buffer Tank 180 during the entire cycle and some of the gas comes direct from the compressor. Valve timing is approximately the same as shown in Table 2 with Valve 205 deleted. The P-V plots for cooling and warm up are similar to figures 5a and 5b.

Figure 4 is a schematic of Pulse Tube Refrigerator 400, which has "active buffer" control. Gas from the compressor flows through Gas Line 110 into the warm end of Regenerator 160 through Valve 120. Gas returns to the compressor from Regenerator 160 through Valve 125 and Gas Line 111. Gas flow to and from the warm end of Pulse Tube 165 comes through Valves 510 and 512, which connect to Buffer Tank 184 and through Valves 520 and 522, which connect to Buffer Tank 182. Buffer Tank 184 is near high pressure, PH, and Buffer Tank 182 is near low pressure, PL.

Table 3 shows the valve timing for cooling in the upper part of the table and for warm up in the lower part of the table. The standard active buffer control system that is designed solely for cooling would have a single valve, Valve 510, in place of Valves 510 and 512 and a single valve, Valve 520, in place of Valves 520 and 522. In order to have a counter clockwise path for the PV plot, so the pulse tube will quickly warm up, it is necessary to add Valves 512 and 522 and shift their timing relative to the other valves.

Figure 6 is a cross section of dual rotary valve Assembly 400 that can implement the P-V plot shown in figures 5a and 5b. Assembly 400 is comprised of a fixed Valve Plate 430, primary Valve Disc 410, secondary Valve Disc 420 Drive Shaft 490, Drive Pins 402, Springs 406, spring Retainer Pins 402, and Enclosure 480.

A top view of Valve Plate 430 is shown in FIG. 6a. Valve Plate 430 has a center hole 432, through which Drive Shaft 490 and high-pressure gas pass, Port 430 which connects to low-pressure return line 111, Port 436 which connects Valve Disc 410 to the warm end of Regenerator 160, and Port 438 which connects Valve Disc 420 to the warm end of Pulse Tube 165.

Figure 6b shows a top view of Valve Disc 410 as it is rotating in a clockwise direction. Drive Pin 402a, which is engaged in Slot 412, drives Valve Disc 410. A mechanism to center the valve discs on Shaft 490 without blocking the flow of high-pressure gas is not shown. The face of Valve Disc 410 that is in contact with Valve Plate 430 has slots that alternately connect the high-pressure supply and low-pressure return gas to Port 436.

With reference to Table 1 "Cooling", Valve Disc 410 is shown at 225° with Valve 125 (Figure 1) just opening. The slot shown in cross section A-A connects the warm end of Regenerator 160 to low-pressure Port 434 for about 125°. Figure 6b shows the slot that affects the open period for Valve 120. This slot connects the high-pressure supply from Line 110 to the warm end of Regenerator 160 for about 125°. High-pressure gas 110 acting on the back side of Valve Disc 410 and low-pressure gas 111 in the slot on the face create a pressure difference during operation that results in a force that seats Valve Disc 410 against Valve Plate 430. Prior to starting the compressor Spring 406a, which is retained by Pin 404a, holds Valve Disc 410 against Valve Plate 430 with sufficient force to get an initial seal.

Figure 6c shows a view from the back of Valve Disc 420 as it is rotating in the same direction as Valve Disc 410. Drive Pin 402b engages Faces 422 to drive Valve Disc 420. The gap between Faces 422 and 424 can be thought of as a slot like 412 that has been enlarged. The face of Valve Disc 420 that is in contact with Valve Plate 430 has slots that alternately connect the high-pressure supply and low-pressure return gas to Port 438. With reference to Table 1 "Cooling", Valve Disc 420 is shown at 225°, with Valve 915 (FIG. 1) open. The slot shown in cross section B-B connects the warm end of Pulse Tube 165 to low-pressure Port 434 for about 90°.

Figure 6c shows the slot that affects the open period for Valve 910. This slot connects the high-pressure supply from Line 110 to the warm end of Pulse Tube 165 for about 90°. High-pressure gas 110 acting on the back side of Valve Disc 420 and low-pressure gas 111 in the slot on the face create a pressure difference during operation that results in a force that seats Valve Disc 420 against Valve Plate 430. Prior to starting the compressor Spring 406b, which is retained by Pin 404b, holds Valve Disc 420 against Valve Plate 430 with sufficient force to get an initial seal.

Rotation of Valve Discs 410 and 420 in the direction shown in figures 6b and 6c produces cooling as shown in figure 5a. Figures 6bb and 6cc show Valve Discs 410 and 420 being turned


in the opposite direction by having reversed the direction of rotation of Drive Shaft 412. Valve Disc 410 is shown in the same position as in figure 6b but Drive Pin 402a is acting on the other side of Slot 412. Valve Disc 420, on the other hand, is shown rotated about 90° , with Drive Pin 402b now acting on Faces 424. The shift in angular position of Valve Disc 420 relative to Valve Disc 410 affects the valve timing shown in table 1 under "Warm Up" and results in the P-V plot shown in Figure 5b.

Figure 6 shows a valve assembly that executes one cycle of the pulse tube with one revolution of the valve. This was done to keep the drawing simple. In actual practice it is more common to have two cycles of the pulse tube for each revolution of the valve discs in order to have the valve face wear more uniformly. Valve assemblies similar to the one shown in Figure 6 can also be made to implement the valve timing in the cooling and warm up modes shown in Tables 2 and 3. Similar valve assemblies can be made for two stage pulse tubes that would provide cooling in one direction of rotation and heating in the other.


CLAIMS

1. A method of shifting a G-M type pulse tube from a cooling mode to a warming mode using valves to change the phase relationship of the flow to the warm end of the regenerator relative to the flow to the warm end of the pulse tube.
2. A pulse tube refrigerator, comprising at least one regenerator, at least one pulse tube, a connecting tube, a first gas line, a second gas line, a first valve 120, a second valve 125, a third valve 910, a fourth valve 915, a cold heat station, and a hot heat station wherein the first gas line brings high-pressure gas from a compressor and the second gas line returns gas at low pressure to the compressor, the first valve 120 admits high-pressure gas to the warm end of the regenerator and the second valve 125 returns gas from the warm end of the regenerator to the compressor; third valve 910 admits high-pressure gas to the warm end of the pulse tube and the fourth valve 915 returns gas from the warm end of the pulse tube to the compressor; the connecting tube connects the cold end of the regenerator with the cold end of the pulse tube such that heat is picked up at the cold end of the pulse tube in the cold heat station and transferred to ambient temperature from the hot heat station or returned to the compressor through the fourth valve 915

cooling is produced at the cold end of the pulse tube refrigerator when the valve timing is approximately



and when the timing of opening and closing valves 910 and 915 relative to valves 120 and 125 is changed to



work energy transfers from ambient temperature to the cold end of pulse tube 165 causing the cold end of pulse tube 165 to warm up.

3. The refrigerator of claim 2 also comprising a buffer tank connected to the warm end of pulse

tube through a flow restrictor or a fifth valve 205 that controls the timing of flow in and out of the buffer tank and to the line connecting valves 910 and 915.

4. The refrigerator of claim 3 where a fifth valve 205 is used for timing of flow and the valve timing for the normal cooling mode is

	120 Open				125 Open		
205				205			
	190 Open				915 Open		
0°	90°	180°	270°	360°			

and for the warm up mode is

	120 Open				125 Open		
		205				205	
915			910 Open				915
0°	90°	180°	270°	360°			

5. The refrigerator of claim 3 where the buffer tank is connected to the warm end of pulse tube through a flow restrictor.

6. A pulse tube refrigerator with active buffer control, where shifting a G-M type pulse tube from a cooling mode to a warming mode using valves changes the phase relationship of the flow to the warm end of the regenerator relative to the flow to the warm end of the pulse tube and where gas from the compressor flows through a first gas line into the warm end of a regenerator through a first valve 120, gas returns to the compressor from regenerator through a second valve 125 and a second gas line, gas flow to and from the warm end of pulse tube comes through a third valve 510 and a fourth valve 512 which connect to a first buffer tank and through fifth valve 520 and sixth valve 522 which connect to a second buffer tank.

7. The refrigerator of claim 6 where the valve timing for the normal cooling mode is

	120 Open				125 Open		
			510				520
512				522			
0°	90°	180°	270°	360°			

and the valve timing during warm up mode is

	120 Open				125 Open		
			510				520
	522				512		
0°		90°		180°		270°	360°

8. A GM type pulse tube refrigerator, comprising a regenerator having a warm end and a cold end, a pulse tube having a warm end and a cold end, the cold end of the pulse tube being connected to the cold end of the regenerator, and a valve mechanism that cycles gas flow to the warm end of the regenerator and to the warm end of the pulse tube, where the phase relation of gas flow to the regenerator and to the pulse tube produces one of cooling or heating at the cold end of the pulse tube depending on the configuration of the valve mechanism.

9. A pulse tube refrigerator as in claim 8 where said valve mechanism consists of a primary rotary disc and a secondary rotary disc on a common drive shaft.

10. A valve mechanism as in claim 9 where the angular position of said secondary disc shifts relative to said primary disc when the direction of rotation is reversed.

11. A pulse tube refrigerator as in claim 8 wherein a cryopanel is attached to a heat station at the cold end of said pulse tube.

12. A pulse tube refrigerator with a cryopanel as in claim 11 wherein said change of phase relation is used to warm-up the cryopanel.

1/5







FIG. 1

DT15 Rec'd PCT/PTO 0 2 JUL 2004

THIS PAGE BLANK (USPTO)



2/5



DT15 Rec'd PCT/PTO 0 2 JUL 2004


THIS PAGE BLANK (USPTO)

3/5



DT15 Rec'd FCT/PTO 0 2 JUL 2004





THIS PAGE BLANK (USPTO)




DT15 Rec'd PCT/PTO 0 2 JUL 2004

THIS PAGE BLANK (USPTO)

5/5



SHOWN AT 225 DEG.



DT15 Rec'd PCT/PTO 0 2 JUL 2004

THIS PAGE BLANK (USPTO)

INTERNATIONAL SEARCH REPORT

International application No.

PCT/US03/06580

A. CLASSIFICATION OF SUBJECT MATTER

IPC(7) : F25B 9/00
US CL : 62/6, 324.1, 160

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
U.S. : 62/6, 324.1, 160

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched
None

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)
None

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y,P	US 6,397,605 B1 (PUNDAK) 04 June 2002 (04.06.2002), see abstract and col 2 lines 47-54.	1,8,9,11,12
Y	US 6,094,921 A (ZHU et al) 01 August 2000 (01.08.2000), see figures 6,9 and 11.	1,8,9,11,12
Y	US 6,308,520 B1 (INOUE et al) 30 October 2001 (30.10.2001), see figure 10.	9
Y	US 4,485,631 A (WINKLER) 04 December 1984 (04.12.1984), see entire document.	11,12
A	US 6,205,792 B1 (ANDERSON) 27 March 2001 (27.03.2001), see entire document.	1-12
A	US 6,301,902 B1 (ZHU et al) 16 October 2001 (16.10.2001), see entire document.	1-12

☐ Further documents are listed in the continuation of Box C.

☐ See patent family annex.

* Special categories of cited documents:	
"A" document defining the general state of the art which is not considered to be of particular relevance	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
"E" earlier application or patent published on or after the international filing date	"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
"O" document referring to an oral disclosure, use, exhibition or other means	"&" document member of the same patent family
"P" document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search

11 June 2003 (11.06.2003)

Date of mailing of the international search report

11 JUL 2003

Name and mailing address of the ISA/US

Mail Stop PCT, Attn: ISA/US
Commissioner for Patents
P.O. Box 1450
Alexandria, Virginia 22313-1450

Facsimile No. (703)305-3230

Authorized officer

William C Doerrler
Telephone No. (703) 308-0861

THIS PAGE BLANK (USPTO)